We claim:

- A process for preparing a catalyst solid for olefin polymerization by bringing 1.
- 5 A) at least one organic transition metal compound,

EPO - DG 1

14. 07. 2004

at least one organometallic compound of formula (V) B)

 $M^{1}(R^{1})_{r}(R^{2})_{s}(R^{3})_{t}$ **(V)**

10

where

 M^1 is an alkali metal, an alkaline earth metal or a metal of group 13

of the Periodic Table,

15

is hydrogen, C₁-C₁₀-alkyl, C₆-C₁₅-aryl, halo-C₁-C₁₀-alkyl, halo- R^1

C₆-C₁₅-aryl, C₇-C₄₀-arylalkyl, C₇-C₄₀-alkylaryl, C₁-C₁₀-alkoxy or

halo-C7-C40-alkylaryl, halo-C7-C40-arylalkyl or halo-C1-C10-alkoxy,

R² and R³ 20

are each hydrogen, halogen, C1-C10-alkyl, C6-C15-aryl, halo-C1-C10-alkyl, halo-C6-C15-aryl, C7-C40-arylalkyl, C7-C40-alkylaryl, C1-C10-alkoxy or halo-C7-C40-alkylaryl, halo-C7-C40-arylalkyl or

halo-C1-C10-alkoxy,

25 r is an integer from 1 to 3

and

s and t

are integers from 0 to 2, where the sum r+s+t corresponds to the

valence of M¹,

at least one organic compound having at least one functional group containing C) active hydrogen, wherein the functional group is selected from the groups consisting of hydroxyl groups, primary and secondary amino groups, mercapto groups, silanol groups, carboxyl groups, amido groups and imido groups,

at least one Lewis base and D)

E) at least one support,

40

30

35

ART 34 AMOT

10

15

into contact with one another, wherein the components are combined in any order without any isolation of an intermediate.

- A process for preparing a catalyst solid for olefin polymerization as claimed in claim 1,
 wherein the component B) used is a mixture of at least two different organometallic compounds.
 - 3. A process for preparing a catalyst solid for olefin polymerization as claimed in claim 2, wherein the component B) used is a mixture of at least one aluminum-containing organometallic compound and at least one boron-containing organometallic compound.
 - A process for preparing a catalyst solid for olefin polymerization as claimed in claim 2 or 3, wherein the component B) comprises at least two different aluminum-containing organometallic compounds.
 - A process for preparing a catalyst solid for olefin polymerization as claimed in any of claims
 to 4, wherein the functional groups containing active hydrogen of the component C) are
 hydroxyl groups.
- 20 6. A process for preparing a catalyst solid for olefin polymerization as claimed in claim 5, wherein the component C is a compound of formula (VI)

$$(R^4)_x$$
—A— $(OH)_y$ (VI)

where

- 25
 - A is an atom of group 13, 14 or 15 of the Periodic Table or a group comprising from 2 to 20 carbon atoms,
- are identical or different and are each, independently of one another, hydrogen,
 halogen, C₁-C₂₀-alkyl, C₁-C₂₀-haloalkyl, C₁-C₁₀-alkoxy, C₆-C₂₀-aryl, C₆-C₂₀haloaryl, C₆-C₂₀-aryloxy, C₇-C₄₀-arylalkyl, C₇-C₄₀-haloarylalkyl, C₇-C₄₀-alkylaryl or
 C₇-C₄₀-haloalkylaryl or R⁴ is an OSiR₃⁵ group, where
- are identical or different and are each hydrogen, halogen, C₁-C₂₀-alkyl, C₁-C₂₀-alkyl, C₁-C₂₀-aryl, C₆-C₂₀-haloaryl, C₆-C₂₀-aryloxy, C₇-C₄₀-arylalkyl, C₇-C₄₀-haloarylalkyl, C₇-C₄₀-alkylaryl or C₇-C₄₀-haloalkylaryl,
 - y is at least 1 and
- 40 x is an integer from 0 to 41.

ART 34 AMOT